

S U P P L Y I N G C L E A N A I R T O I N D U S T R Y

New!

MODEL M72

In-duct MicroGlass Air Cleaner



The new M72 is an in-duct media air cleaning system. It features the MicroGlass Extended Service Filters for long filter life and high efficiencies to effectively remove smoke, mist, dust and other airborne contaminants at a rate of up to 6000 cubic feet of air per minute. Multiple units can be used for additional capacity.




For further information:
BERRIMAN ASSOCIATES
1-800-480-3630
www.berriman.com



M72 FEATURES & SPECIFICATIONS

FEATURES

- Extended service life due to large filter media surface area of 400 sq. ft. total.
- Low filter pressure drop for reduced energy consumption and cost.
- Air flow capacity up to 6000 cubic feet per minute.
- High contaminant-holding capacity that results in low maintenance (fewer change-outs) and disposal costs.
- Increased efficiency during service life (no particle migration or fiber breakoff).
- Higher recommended final pressure drop (longer filter life) than conventional bag filter systems.
- Stacking capacity up to 36,000 CFM with optional hardware.



UNIT PERFORMANCE



SPECIFICATIONS

DIMENSIONS: 21" L x 49.5" W x 32.25" H

WEIGHT: Installed: 137 lbs.
Shipping: 162 lbs.

CABINET: 16 gauge galvanized steel.

PRIMARY FILTER: Rigid V-bank, mini-pleated microglass fiber construction. Two 23^{3/8}" x 23^{3/8}" x 11^{1/2}" filters in each unit. Filters weigh 13.25 lbs. each with a total collection area of 400 sq. ft.


AMBIENT TEMPERATURE: 175°F maximum.

MOUNTING: Standing or hanging cabinet with horizontal or vertical airflow. Ceiling mount brackets are standard.

PREFILTER: Two 30-35% efficiency pleated prefilters, 24" x 24" x 4". Filter media is a cotton and synthetic blend. Total prefilter media area is 59 sq. ft.

INSTRUMENTATION: Dirty Filter Gauge designed to determine filter replacement cycle.

FILTER ACCESS: Side load track system with hinged access door.



For further information:
BERRIMAN ASSOCIATES
1-800-480-3630
www.berriman.com

Manufacturer has a policy of continuing product improvement, and reserves the right to make changes in design and specification without notice.